15'-8"		20 Ib ROOF LOAD SIDEWALL OPENING (FT) SIDEWALL OPENING PIER LOAD 16' BOX WIDTH 1244 1413 1581 1750 2088 2425 *FOR 30 Ib & 40 Ib ROOF LOAD REFER TO TABLES 7 & 7g IN THE INSTALLATION MANUAL.
		SIDEWALL OPENING (FT) REQUIRED PIER LOAD (LBS) 4 5 6 8 1413 1581 1750 2088 COMBRES 7 & 7a IN THE INSTALLATION
D - 47.4.	#6:71/2" REAR [#3:5]	10 2425 N MANUAL.
	7 1/2" REAR DOOR PIERS 1 42:19 1 42:103/4" 72" 1 41:41/2" 1	
30:7"		
93½"		
441/4" 991/27/	441/4"	

ω 4. τ

CHARTS (TABLE 18, 19, AND 20).

3. THE MAXIMUM SPACING FOR 8" I-BEAMS IS 8 FEET, 10" & 12" I-BEAMS IS 10 FEET.

4. SERVICE DROP LOCATIONS IDENTIFIED ARE APPROXIMATE.

5. FLOOR WIDTH SHOWN IS FOR STANDARD PRODUCT ONLY. CONTACT THE MFG FACILITY FOR SPECIFICATIONS OF OPTIONS ORDERED.

PIER LEGEND

- TYPICAL FRAME SUPPORT PIERS

PIER PORCH/RECESSED ENTRY PIER PERIMETER

SERVICE DROP LEGEND

E = ELECTRICAL DROP

W = WATER INLET

ର D = DWV PLUMBING DROP

OPT FRAME PIERS roduct Designer: Alex Whaley CMH MANUFACTURING Model #: MXR | 67635

Date: 2.2.15 | Scale: N.T.S. 16' x 80' Maxımızer (5) 3 REVISION ECR-458602 4.4.17 ACW Drawing #: 315156

1,254 SQ.FT. (STD PLAN "CONDITIONED")